AS363

Slow-whoop, 9 - 60VDC, afname tussen 4-41mA @ 24VDC, 88 tot 106dB 1m.



AS363

Slow-whoop, 9 - 60VDC, afname tussen 4-41mA @ 24VDC, 88 tot 106dB 1m.

Technische specificaties

Electrical

Power supply type	VDC
Number of connection terminals	3

Physical

Colour	Rød
Mounting type	Samling på underlag
Mounting position	Base, Decke, Wand
Mounting base	Flach
Material	Høj slag polykarbonat

Environmental

Vandal proof	No
Environment	Indendør

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Compatibele producten

Categorie	Referentie	Beschrijving
Notification device	AS363W	Slow-whoop, 9- 60VDC, uitgang 88 -106dB(A) temp. van -25º tot +70º C ,IP21
Notification device	AS364	Slow-whoop met montagevoet voor pijpinvoer, temp. van -25º tot +70º C, IP65
Notification device	AS364W	Slow-whoop met montagevoet voor pijpinvoer,temp. -25º tot +70º C, IP65, wit
Notification device	AS36RIM	FIRE Label voor AS360, AS2360, FA360 en FA2360 Slow-Whoops en Flitsen

EDWARDS
Built for Resilience

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57