# PB21

## 2m - 360° AIR Beam Tower (double sided) including installation kit

### Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 2 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP4)
9. M4x20 DIN 933 : 2 pcs (EP2)
10. M4 DIN 934 : 20 pcs (EP4) (C3)
11. M4 DIN 985 : 2 pcs (EP2)
12. M4 DIN 125 : 2 pcs (EP2)
13. Spacer : 2 pcs (EP2)
14. Cable gland PGM16 : 2 pcs (EP4)
15. Cable gland PGM20 : 2 pcs (EP4)
16. M8x16 DIN933 : 4 pcs (TA3)
17. Side bracket <2m : 2 pcs
18. M8 DIN 985 : 4 pcs (TA3)
19. M8 DIN 125 : 4 pcs (TA3)
20. M4x12 DIN 7985 : 16 pcs (C3)
21. Bracket : 8 pcs
22. dia.2.9x16 DIN 7981 : 16 pcs (C3)
23. Anchor bolt : 4 pcs (MAN2)



### Details

- 2m height
- 360° view
- CE certified product

# PB21

## 2m - 360° AIR Beam Tower (double sided) including installation kit

## Technical specifications

### General

| | |
|---|---|
| Accessory group | Perimeter / Outdoor |
| Type | Mounting |

### Electrical

| | |
|---|---|
| Power supply type | VDC |
| Operating voltage | 12 to 24 V |

### Physical

| | |
|---|---|
| Physical dimensions | 1970 x 130 x 260 mm |
| Net weight | 7.50 kg |
| Material | Aluminium, Polycarbonate / ABS |

### Environmental

| | |
|---|---|
| Operating temperature | -15 to 50°C |

### Detection

| | |
|---|---|
| Angle of view | 360° |

### Output

| | |
|---|---|
| Tamper switch | CO (change over) |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 April 2024 - 16:02