9-30802


AirSense Stratos Remote Display Unit (RDU)

Description

The Remote Display Unit (RDU) is a LED bargraph repeater and status display, which is used to remotely mimic the status of a Stratos ASD. It comes in 19” rack format, that allow for multiple units to be mounted next to each other in a 19" rack, or individually with the support of the 9-30817 housing.

The RDU is connected onto the SenseNET bus which provide the data flow between the unit and the ASD. A bank of switches selects the detector whose display is to be repeated. The unit is powered from a 24V DC nominal power supply.

The RDU provide by way of LED's basic ok and faults indication, 4 alarm levels, and a bargraph display which show the level of obscuration. The RDU can also be expanded with a relay card (9-30803) which provide relay output for the 4 alarms flags and fault indication.



Details

- LED status indication & bargrpah display
- 19" rack mount support
- Optional relay expansion

9-30802
AirSense Stratos Remote Display Unit (RDU)

Technical specifications

General

Status indication	LED

Electrical

Operating voltage	18 to 30 VDC
Current consumption	40 mA

Physical

Physical dimensions	53 x 130 x 31 mm (W x H x D)

Environmental

Operating temperature	-10 to +60°C
Relative humidity	0 to 90% noncondensing
Environment	Indoor

Outputs

Expansion	Optional relay card

Networking

SenseNET (RS-485)	Onboard

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 28 July 2025 - 15:20