# ATS1192X4

**Pack de 4 ATS1192.**



# ATS1192X4

**Pack de 4 ATS1192.**

## Especificaciones técnicas

### System

| | |
|---|---|
| Supported card types | HiTag2 |
| Addressing type | Card Addressing, Keypad Addressing, Software Addressing |

### Technology

| | |
|---|---|
| Reader type | Proximity, Smart Card |
| Reader operating-transmitting frequency | 125 KHz |
| Supported technology 125 kHz | HiTag 2 |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485, Wiegand |
| Connector type | Pigtail |

### Inputs/outputs

| | |
|---|---|
| Inputs | Request to exit |
| Outputs | 1 Open Collector (25 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| PIN keypad | No |

### Physical

| | |
|---|---|
| Colour | Dark grey |
| Mounting Type | Surface mount |

### Environmental

| | |
|---|---|
| Environment | Outdoor |

Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57