PM812N-G2

Power supply switch mode, 12 VDC, 1.4 A, EN Grade 2

Certified Gr.2

Suitable for use in systems designed to comply with EN50131-6:2008 Grade 2 and Environmental Class II, requiring 18Ah standby battery capacity.

Protection

Comprehensive protection is built-in as standard including mains transient filtering, electronic output overload protection and fuses on the load and battery outputs.



Details

- Fault signals for loss of mains, power supply fault and battery low voltage warning
- Battery deep discharge protection
- Tamperswitch
- Protection against reverse battery connection
- Thermal protection of power circuitry
- LED's for comprehensive diagnostics
- Powder coated steel housing
- EN50131-6:2008 Grade 2 Type A certified

PM812N-G2

Power supply switch mode, 12 VDC, 1.4 A, EN Grade 2

Technical specifications

General

Fuse(s)	Load: F1.6 A, Batt: F1.6 A
Deep discharge protection	Battery disconnect @ 10.6 V battery terminal voltage
Protection	Reverse battery connection protection

Electrical

Mains input	100 to 240 VAC

Output

Power output voltage	13.8 VDC
Output ripple	<400 mV pk – pk max. @ rated voltage
Power output current mains	1.5 A

Battery

Max. Battery capacity	18 Ah 12 V
Power output current battery	12 hours 1.5 A with 18 Ah battery
Battery recharge time	<72 hours to 80%

Physical

Physical dimensions	330 x 275 x 80 mm (W x H x D)
Net weight	3.3 kg (without battery)
Colour	Weiß
Material	Stahl
Form factor	Stahlschrank
Housing (steel) powder coated	1.2 mm

Environmental

Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C

Regulatory

EN50131 Grade	Klasse 2
Compliancy	CE, REACH, RoHS 2, WEEE
Certification	EN50131 Grad 2
	EN50131-6:2008 Grade 2 Type A
	Environmental Class II

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 15:17