# ACL585

## Vandal proof slim keypad, moulded aluminum, standalone

### Standalone vandal-proof keypad

Mullion and vandal-resistant access control keypad with metal keys for doorframe mounting. With user memory of 1000 codes and one push button, ACL585 is the best solution for single door access control. Photoelectric sensor for automatic illumination is effective in low-lit conditions. ACL585 with a rugged good look is designed to operate even in harsh environments.




### Einzelheiten

- Indoor/outdoor
- Slim moulded aluminum housing with metal keys
- Dust proof and water-resistant
- Up to 1000 user codes
- Request To Exit using normal RTE button or ACL870 type pushbutton
- Codes can be 1 to 8 digit long
- 30 second lockout after eight consecutive invalid PINs

# ACL585

## Vandal proof slim keypad, moulded aluminum, standalone

## Technische Spezifikationen

### General

| | |
|---|---|
| User interface | Touch-Tasten |
| Product line | Autonome |

### Communication

| | |
|---|---|
| Communication type | Verdrahtet |

### Inputs/Outputs

| | |
|---|---|
| Inputs | 1 |
| Input type | Request-to-exit |
| Outputs | 1 |
| Output type | SPDT relay, latch or pulsed mode (01 to 99 seconds) |

### Electrical

| | |
|---|---|
| Operating voltage | 12 / 24 VAC/VDC |
| Current consumption | 70 mA max. |

### Physical

| | |
|---|---|
| Physical dimensions | 150 x 50 x 25 mm |
| Form factor | Vertikal |
| Mounting type | Montaje en Superficie |
| Material | Geformtes Aluminium |

### Environmental

| | |
|---|---|
| Operating temperature | -25 to +50°C |
| Relative humidity | 95% noncondensing |
| IP rating | IP65 |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CE |

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.