# FD2705R

**Analoge Beam detect., reflector principe, max. detectie afstand is 50 meter.**



# FD2705R

**Analoge Beam detect., reflector principe, max. detectie afstand is 50 meter.**

## Technische specificaties

### General

| | |
|---|---|
| Addressing method | DIP Switches |

### Electrical

| | |
|---|---|
| Power supply type | Loop powered |

### Detection

| | |
|---|---|
| Optical wave length | 880 nm |

### Physical

| | |
|---|---|
| Colour | Black, Grey |
| Mounting type | Wall mount |
| Material (body) | Flame retardent ABS |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Environment | Indoor |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 3, WEEE |
| Certification | CPR |

### Compatibele producten

| Categorie | Referentie | Beschrijving |
|---|---|---|
| Detection device | FD-MB10 | Montage voet voor gebruik met de FD700, FD900, FD2700 en FDR-EZ series |
| Detection device | OR2000 | Opt. mech. Reflector voor FD705/710RVDS en FD2000/2010 beam rookdetec |

KIDDE GLOBAL SOLUTIONS

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57