SMA-L-MULTI

MA SIGMA Lite - Multi, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, 500 users, IP65, CE



SMA-L-MULTI

MA SIGMA Lite - Multi, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, 500 users, IP65, CE

Especificações técnicas

System

RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	Yes

Technology

Reader type	Biométrico
Reader operating-transmitting frequency	13,56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE Classic (datos personalizados), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (datos personalizados), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE Plus (CSN, niveles 1 y 3), NFC (CSN)
SAM module embedded	No

Biometric

Biometric type	Huella digital
Biometric sensor type	Óptica

Interface & connections

Interface	Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand
Connector type	Netzwerk, Zopf

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	Yes
PIN keypad	No

Electrical

Power supply type	VCC

Physical

Colour	Schwarz
Material	Polycarbonat
Form factor	Überdimensioniert
Mounting type	Montaje en Superficie

Environmental

Vandal proof	No

Regulatory

Compliancy	CE, FCC, REACH, RoHS



Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57