FAW355WC

Conventional VAD, Deep Base, Wall Mount - White Flash

General

The FAW355W is a general purpose wall mount LED beacon for fire alarm applications. It features a special deep base containing all wiring connections and allow for easy removal/placement of the device. With an EN54-23 approved coverage pattern of W-3.1-11.3, each FAW355WC may be mounted up to 3.5m high and cover a square room of 11.3 x 11.3m with a single device.



Easy and Fast Installation

The FAx350 beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these becons use a deep base version of the TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The FAx350 beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area. The flash rate of the beacon may be adjusted during installation, with a selection of 0.5Hz or 1Hz.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the beacon from the base.

Details

- Automatic syncronisation
- Anti-Tamper locking mechanism
- Deep mouting base
- Wiring directly to base
- Flash rate selectable
- IP65 Ingress protection

FAW355WC

Conventional VAD, Deep Base, Wall Mount - White Flash

Technical specifications

General

Line monitoring	Polarised input

Electrical

Operating voltage	17 to 60 VDC
Current consumption	20 mA @ 0.5 Hz / 40 mA @ 1 Hz

Sounder

Output level	Continuous operation
Synchronization	Phased start (Automatic)

VAD

Colour	White
Flash frequency	0.5 Hz or 1 Hz

Physical

Physical dimensions	100 x 104 mm (Ø x D)
Net weight	250 g
Colour	Hvid
Mounting type	Vægmontering
Mounting height	up to 3.1 m
Material	Policarbonato alto impatto

Environmental

Operating temperature	-25 to +70°C
Relative humidity	5 to 95% noncondensing
Environment	Indendør, Udendørs
IP rating	IP65


Regulatory

Certification	EN54-23

EN54-23 rating

Light coverage	W-3.1-11.3
Floor coverage	up to 11.3 m x 11.3 m

EN54-23 Coverage: W-3.5-11.5



KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 15 October 2026 - 16:43