177601

ZP755HA-2R omni sounder, red

General

ZP755HA-2R is a RED addressable horn sounder designed for use with ZP addressable fire alarm systems. Designed with dual front and rear sound paths, it provides an 'all around' sound output - ideal for open area coverage.

Installed directly onto and powered by the ZP wiring loop, the ZP755HA-2 sounders enable the system designer to offer a complete ZP addressable system on a single pair of wires. Installation time and costs are further reduced as the moulding plugs directly into a first fix base – eliminating the need for any internal connections.

The units high efficiency acoustic design, together with a low energy 'sound gun' transducer, enables up to 40 sounders to be connected to a one kilometre loop of 1.5 mm² cable, with a wiring run of 50 metres to the first device.

Self test facility

The range features a unique self test facility - automatically activated during routine sounder testing. A built in microphone circuit measures sound output and automatically signals the sounder address and location to the control panel, should the output test fail.

In systems where loop lengths or current requirements are excessive, ZP755 sounders can be powered directly from an external power supply. All ZP755 sounders incorporate switch settings enabling them to be assigned a unique address, which is polled by the panel every two seconds.

Range of sound outputs

Continuous, intermittent and two-tone outputs are available from which any combination can be chosen to provide alert and evacuate, two stage alarms. Sound types comply with most international codes (e.g. BS 5839 Part 1 recommended frequencies).

ZP755HA-2 sounders produce a sound output of up to 92 dBA (tested at 1 metre). The volume setting can be reduced for areas where a lower sound output is required.

Moulded in high impact thermoplastic, the sounders are available in either polar white, red or white.



Details

- Wide 'all around' sound distribution
- Microphone self test facility
- Plug in base – no direct wiring connections
- Up to 50 sounders directly on the loop wiring
- High efficiency sound gun transducer
- Synchronised outputs
- EN54:3 approved and CPR certified

177601
ZP755HA-2R omni sounder, red

Technical specifications

General

Compatibility	ZP7 series addressable systems
Addressing method	DIP Switches
Monitoring	Device removal, Device type, Open circuit, Short circuit, Sound output

Electrical

Operating voltage	19.5 to 20.5 V (from the loop) 18 to 30 VDC (from an external supply)

Sounder

Output level	<90 dB(A) (tone dependant)
Selectable tones	User configurable

Physical

Physical dimensions	127 x 113 mm (Ø x H)
Net weight	275 g
Colour	Rød
Mounting type	Montaggio su base
Mounting position	Soffitto, Parete
Material	Støbt termoplast

Environmental

Operating temperature	-10 to +60°C
Storage temperature	-20 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indendør
IP rating	IP21C

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54-3

Loop current

Quiescent (when loop powered)	820µA
Active (when loop powered)	6.4mA
Quiescent (when externally powered)	470µA
Active (when externally powered)	500µA

Devices per loop (max)

	50 (1km loop of 1.5mm² cable, 50 m to first device)

Wiring


	2 core loop


Addressing method

	7 way dipswitch

Compatible products

Category	Reference	Description
Notification device	SPB-2R	Plug-in Base, RED





KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 October 2026 - 11:29