71601

ZP3 Series - ZP3-RDUB 1 Repeater Panel - English

Attractive low profile unit

Designed to match the ZP3 main control panel, the ZP3-RDU remote display is an attractive, low profile unit providing repeat indication and system control at a location remote from the main control panel position. Housed in a small, slim enclosure, the remote unit has a fascia design and layout in matching style to ZP3 control equipment. Up to 32 remote units can be connected to any central panel.

The unit features zonal designation for up to 50 zones, a 4 row 160 character, back lit liquid crystal display and an 'at a glance' system status LED matrix. Controls are provided for accept, reset, silence and sound alarms. A restore disabled alarms facility re-enables previously disabled alarm sounders immediately, should the need for an evacuation arise.


Displays both zone and address information

Control keys are provided to select listings of current fires, faults and disablements for display. Initial information is displayed by zone, with a further facility to display point addresses within the displayed zone. Operating as an indicator panel only in its normal mode the ZP3-RDUB1 system control functions are accessed by means of a security key switch. Internal switches are provided to configure the unit to operate as an indicator only with no control facilities, with controls by key access, or with control functions enabled on a permanent basis.

Serial link connection

The unit is driven from an optional serial driver card, added to the main board within the ZP3 panel enclosure. Wiring to the main control panel is by serial link, screened, twisted pair, which can be daisy chained, teed off or spurred. The total wiring length of all remote display units connected to a main control panel can be up to two kilometres.

The ZP3-RDUB1 can either be powered directly from the main panel 24 VDC, or by a remote power supply unit. A version featuring a stainless steel enclosure is also available.



Details

- Remote control and indication
- Up to 32 remote units connected to each main panel
- 4 row 160 character LCD
- Replicates main panel fascia
- Restore disabled sounders facility

71601
ZP3 Series - ZP3-RDUB 1 Repeater Panel - English

Technical specifications

General

Compatibility	All ZP3 analogue addressable panels
Description	Remote display unit
Description	ZP3-RDUB1-24SS - Stainless steel enclosure

Electrical

Operating voltage	24 VDC
Current consumption	100 mA (panel in mains fail state), 250 mA
Wiring	Comms connection by 2 core RS485 screened twisted pair. Total 2km for any number of units per ZP3 main panel
Power supply	From ZP3 control panel or remote PSU

Physical

Form factor	Lille
Physical dimensions	Front plate: 220 x 360 mm (H x W) Back box: 195 x 335 x 60 mm (H x W x D) Overall: front plate projects 20 mm when recessed
Net weight	2.6 kg
Colour	Grigio (Pantone 428c)
Mounting type	Forsænket montering, Montaggio a superficie
Material	Back box and Front plate - sheet steel

Environmental

Operating temperature	-5 to + 40ºC
Relative humidity	10 to 90% noncondensing
Environment	Indendør
IP rating	IP30

Monitoring

	Panel disconnection. LEDs for zone designation (50), power, fire, fault, disabled, other, silence alarms, sound alarms.

Text Display

	4 line 160 character LCD (black lit)

Data interface

	Via ZP3AB-SCB-D (RS485) serial bus driver board

Key switch enable

	All controls (can be software enabled in main panel)

Regulatory

EMC	CE marked (EEC89/336)

Publication No

	PS1294

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 17 June 2025 - 10:57