6030-100

Fireray Hub Reflective - Detector

General

The Fireray Hub Reflective Detector is an additional beam detector head for use the the Fireray Hub Reflective System. Connection of up to 3 Fireray Reflective Detectors can be accommodated on a single cable run to the hub, making the installation extremely easy and flexible.

Benefits

It supports modern, reflective motorised beam technology that facilitates:

• Auto-Alignment™
Using the Hub, direct the laser onto the prism and with the press of a button, it aligns itself.

• Building Movement Tracking™
Keeping the beam aligned even if the building moves, preventing unwanted alarms and faults

• Light Cancellation Technology™
Prevent nuisance alarms by compensating for sunlight and artificial light sources



Details

- Offers laser-assisted, motorised Auto-Alignment™ from the system controller, with manual alignment as an option if needed
- 2-wire interface from detector to system controller offers an installation with 60% less wiring and in 25% less time using network mode
- Compensates for natural shifts in alignment from building movement
- Compensates for gradual build-up of contamination on the optical surfaces
- Compensates for high levels of sunlight and artificial lighting
- Dynamic beam phasing allowing beam detectors to be mounted facing each other with the reflectors in the middle
- Operate in dusty or wet environments due to the high enclosure integrity of the detector

6030-100
Fireray Hub Reflective - Detector

Technical specifications

General

Compatibility	6020-100 Fireray Hub Reflective
Connectivity	2-wire & screen
Addressing method	DIP Switches

Electrical

Power supply type	Alimentato ad anello
Operating voltage	14 to 36 VDC
Cable specification	24 to 14 AWG (0.5 to 1.6 mm) (1/100" to 6/100")
No. of cable cores	2, dedicated

Detection

Detection principle	Optical infrared beam
Zone length	< 100 m from the hub
Range	8 to 50 m (to 120 m with FD-LRK)
Optical wave length	850 nm
Adjustment angle	± 4.5°
Misalignment tolerance	± 0.5°
Beam path clearance	0.5 m (1¾ ft) radius from centre line between detector and reflector
Response time	< 2 s

Physical

Physical dimensions	Detector: 131 x 134 x 131 mm (H x W x D) Reflector: 100 x 100 x 9 mm (H x W x D)
Net weight	Detector: 0.57 kg Reflector: 0.06 kg
Mounting type	Hinged mouting, Montaggio a superficie

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C (+14 to +131ºF)
Storage temperature	-40 to +85°C (-40 to +185ºF)
Relative humidity	0 to 93% non condensing or icing
Environment	Indendør
IP rating	IP55

Regulatory

Compliancy	CE, REACH, RoHS 3, UKCA, WEEE
Certification	CPR
Voluntary marks	VdS
Standards	EN54-12

Compatible products

Category	Reference	Description
Detection device	5000-008	Fireray Reflective short range prism plate
Detection device	6020-100	Fireray Hub Reflective System
Detection device	FD-LRK	Long-range reflector kit for Fireray Beam Detectors (1010-000)
Mounting Accessories	FD-MB001R	Mounting bracket for FD001R beam detectors (6010-100) and 5000-007/5000-008 reflector plates
Mounting Accessories	FD-PC001R	Protective cage for Fireray reflective beam detectors (1100-000)

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 November 2025 - 9:36