SC-13-1100-0001-99

SmartCell intelligent wireless zone monitor. 230V

Wireless Zone Monitor overview

The Wireless Zone Monitor (WZM) has been designed with flexibility in mind, allowing connection to both conventional and addressable fire alarm systems. Supporting up to 16 SmartCell wireless fire devices, communication between devices and the WZM is bidirectional and operates in the European harmonised 868 MHz frequency band.



Details

- Wireless device communication
- Quick and easy to install
- Compact enclosure
- 80 character display
- 24 VDC version also available

SC-13-1100-0001-99

SmartCell intelligent wireless zone monitor. 230V

Technical specifications

Electrical

Power supply type	230 VAC
Operating voltage	220 to 240 VAC, 50 Hz, 0.3 A
Current consumption	5 mA (PSU), plus 100 mA from WZM

Input

Input quantity	2
Input type and rating	Resistor monitored inputs

Output

Output quantity	2
Output type and rating	1x fire & 1 x fault, rated 30 V @ 1 A

Physical

Physical dimensions	275 x 220 x 80 mm (W x H x D)
Net weight	1.55 kg
Colour	Hvid
Mounting type	Montaggio a superficie
Cable entries	4 x 100 mm (bottom) / 4 x 100 mm (back)
Batteries	6 V, 4 Ah

Environmental

Operating temperature	-5 to +45°C
Storage temperature	0 to +30°C
Relative humidity	95% noncondensing max.
Environment	Indendør
IP rating	IP30

Regulatory

Compliancy	CE
Certification	CPR
Standards	EN54-13 EN54-18 EN54-25

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 June 2026 - 9:29