# SC-62-0210-0001-99

## SmartCell Wireless Remote Indicator

### Overview

The SmartCell wireless remote indicator is quick and easy to install and offers individual addressing at the SmartCell control panel.

Features include red fire indication LED, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

- Fully wireless
- Quick and easy to install
- Red fire indication LED
- Unique design
- Inbuilt locking mechanism

# SC-62-0210-0001-99

## SmartCell Wireless Remote Indicator

## Technical specifications

### General

| | |
|---|---|
| Wireless frequency | 868 MHz |
| Compatibility | SmartCell, Excellence Gateway |

### Electrical

| | |
|---|---|
| Power supply type | Batteries |
| Batteries | 3 x 3.6 V lithium thionyl chloride batteries.<br>Fanso: ER14505M<br>HCB: ER14505M (HCB-JS-TZ-02-547) |
| Power consumption | 1.46 W max. |
| Operating voltage | 2.7 to 3.65 VDC |
| Current consumption | 0.1 to 400 mA |

### Physical

| | |
|---|---|
| Physical dimensions | 110 x 39 mm (Ø x D) |
| Colour | White |
| Mounting type | Wall mount |
| Mounting base | Wireless |

### Environmental

| | |
|---|---|
| Vandal proof | Yes |
| Operating temperature | -10 to +55 °C |
| Storage temperature | -10 to +30 °C (with batteries) |
| Relative humidity | 0 to 95% noncondensing |
| Environment | Indoor |
| IP rating | IP21C |

### Regulatory

| | |
|---|---|
| Compliancy | CE |
| Certification | CPR |
| Standards | EN54-13<br>EN54-25 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 May 2026 - 16:37