# ACL800-RDRMF-GRAY

**ACL800 MIFARE READER - WIEGAND, SURFACE MOUNT, BLACK**



# ACL800-RDRMF-GRAY

## ACL800 MIFARE READER - WIEGAND, SURFACE MOUNT, BLACK

## Spécifications techniques

### System

| | |
|---|---|
| Max. reader distance to panel | 152 m |
| RTE (Request To Exit) | No |
| CSN (Card Serial Number) | Yes |
| Custom data model | No |
| No. of LEDs | 1 |
| No. of covers included | 1 |

### Technology

| | |
|---|---|
| Reader type | Smartcard |
| Reader operating-transmitting frequency | 13.56 MHz |
| Supported technology 13.56 MHz | MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE UltraLight (CSN) |
| Mifare type | ISO14443A |
| No. of Mifare bytes CSN | 4 Byte (S50), 7 Byte (S70) |
| Read write | No |
| SAM module embedded | No |

### Interface & connections

| | |
|---|---|
| Interface | Wiegand |
| Connector type | Zopf |
| Pigtail length | 90 cm |

### Tamper type

| | |
|---|---|
| Pry-off tamper | No |
| Opening tamper | Yes |

### Operation

| | |
|---|---|
| Stand-alone | No |
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Power supply type | VDC |
| Power supply value | 5 to 24 VDC |
| Current consumption | 100 mA at 24 VDC<br>30 mA at 24 VDC |

### Physical

| | |
|---|---|
| Net weight | 120 g |
| Shipping weight | 170 g |
| Colour | Schwarz |
| Material | ABS |
| Form factor | Mullion |
| Mounting type | Montaggio a superficie |

### Environmental

| | |
|---|---|
| Environment | Drinnen, Draussen |
| Storage temperature | -20 to +50°C |

### Regulatory

| | |
|---|---|
| Compliancy | CE, RoHS |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57