SMA-LP-MULTI

MA SIGMA Lite Plus - Multi, 2.8 inch QVGA touchscreen, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, IP65, 500 users, CE



SMA-LP-MULTI

MA SIGMA Lite Plus - Multi, 2.8 inch QVGA touchscreen, Multi-factor Bio/Card, MIFARE/MIFARE Plus/DESFIRE, IP65, 500 users, CE

Especificaciones técnicas

System

RTE (Request To Exit)	No
CSN (Card Serial Number)	Yes
Custom data model	Yes

Technology

Reader type	Biometryczny
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE Classic (własne dane), MIFARE DESFire (CSN), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (własne dane), Mifare DESFire EV2 (CSN), MIFARE Plus (CSN), MIFARE Plus (CSN, poziom 1 i 3), NFC (CSN)
SAM module embedded	No

Biometric

Biometric type	Linie papilarne
Biometric sensor type	Optyczny

Interface & connections

Interface	Ethernet, OSDP V2, OSDP V2 Sicherer Kanal, RS-485, USB, Wiegand
Connector type	Netzwerk, Zopf

Tamper type

Pry-off tamper	No
Opening tamper	Yes

Operation

Stand-alone	Yes
PIN keypad	Yes

Electrical

Power supply type	PoE-Eingang

Physical


Colour	Schwarz
Material	Polycarbonat
Form factor	Überdimensioniert
Mounting type	Montaż nawierzchniowy

Environmental

Vandal proof	No
Environment	Draussen

Regulatory

Compliancy	CE, FCC, ICASA, REACH, RoHS, UL 294, WEEE



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 12 November 2026 - 18:57