ATS1192X4

4 pack ATS1192 Heavy-duty smart card reader with 2.5 m cable



ATS1192X4

4 pack ATS1192 Heavy-duty smart card reader with 2.5 m cable

Spécifications techniques

System

Max. reader distance to panel	1500
Supported card types	HiTag2
Addressing type	Cartão de endereçamento, Endereçamento Teclado, Endereçamento Software
No. of LEDs	Bicolor

Technology

Reader type	Nahdistanz, Smart Card
Reader operating-transmitting frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Interface & connections

Interface	ATS RS-485, Wiegand
Connector type	Zopf
Pigtail length	250

Inputs/outputs

Inputs	Pedido de saída
Outputs	1 Coletor Aberto (25 mA)

Tamper type

Pry-off tamper	Yes

Operation

PIN keypad	No

Electrical

Power supply value	9 to 14 VDC
Current consumption	80 25

Physical

Physical dimensions	42 × 150 × 16 mm
Colour	Cinzento escuro
Mounting Type	Montagem em superfície

Environmental

Operating temperature	-35 to +66 °C
Environment	Draussen
IP rating	IP54

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57