ATS1190

Advisor Master Smart Card Proximity-lezer. Kleur wit



ATS1190

Advisor Master Smart Card Proximity-lezer. Kleur wit

Technische specificaties

System

Supported card types	HiTag2
Addressing type	Cartão de endereçamento, Endereçamento Teclado, Endereçamento Software
Reader accessory	Cores de coberturas opcionais

Technology

Reader type	Nærhed, Smart Card
Reader operating-transmitting frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Interface & connections

Interface	ATS RS-485, Wiegand
Connector type	Svinesvans

Inputs/outputs

Inputs	Pedido de saída
Outputs	1 Coletor Aberto (25 mA)

Tamper type

Pry-off tamper	Yes

Operation

PIN keypad	No

Physical

Colour	Hvid
Material	Plastic
Mounting Type	Montagem em superfície

Environmental

Vandal proof	No
Environment	Indendør, Udendørs

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57