# ATS1475

## Proximity card packed by 10-pack

### Product overview

These cards are to be used on ATS readers. The cards are unprogrammed and have the number printed for easier administration. Both the smart ship and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.




### Details

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- Packed by 10

# ATS1475

## Proximity card packed by 10-pack

## Technical specifications

### System

| | |
|---|---|
| Reading distance | 0 to 60 cm |
| Custom data model | No |
| Supported readers | ATS Proximity Readers |

### Technology

| | |
|---|---|
| Credential type | Nærhed |
| Credential operating frequency | 125 KHz |
| Supported technology 125 kHz | HiTag 2 |

### Printing

| | |
|---|---|
| Direct surface printing | Yes |

### Ordering information

| | |
|---|---|
| Minimum order quantity | 1 |
| Cards/tags in package | 10 |

### Physical

| | |
|---|---|
| Material | PVC |
| Form factor | CR80 (Credit) |
| Physical dimensions | 86 x 54 mm |
| Colour | Hvid |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:24